



# CP-1 PLUS

## TEMPERATURE CONTROL



Temperature range -20°C to +300°C (according to models).  
New gap adjustment ring.  
Compatible from FIRST PLUS.  
Removable lower plate.  
Temperature ramp programming (optional).

# Activity domains



Chemical / petroleum products



Paint / ink / coatings

AVAILABLE TEMPERATURE CONTROL DEVICES (Not compatible with B-ONE and LR version device)

Compatible with bayonet and AC 265 coupling

Designation	Part Number	Temperature range	Type	Need Circulator <sup>a)</sup>	Prog <sup>b)</sup>	Compatible device	Compatible Measuring system	Size (pxlxh) in mm	Weight
CP-1 PLUS	N401000	+10°C to +70°C	Peltier	No	No	FIRST, RM100 <sup>c)</sup> , RM200	MS CP	610x340x650	15Kg
CP-1 PLUS	N401100	+10°C to +70°C	Peltier	No	Yes				
CP-1 PLUS	N401200	+10°C to +100°C	Peltier	No	No				
CP-1 PLUS	N401201	+10°C to +100°C	Peltier	No	Yes				
CP-1 PLUS	N401300	-20°C to +100°C	Peltier	Yes	No				
CP-1 PLUS	N401301	-20°C to +100°C	Peltier	Yes	Yes				
CP-1 PLUS	N404000	Room to +300°C	Electrical	No	No				
CP-1 PLUS	N405000	Room to +300°C	Electrical	No	Yes				

a) Circulator not included. Need for cooling of liquid Peltier

b) Allow programming of temperature ramp

c) Not compatible with Portable RM100 and RM100 i