



# EVA LR-BV PLUS

**TEMPERATURE  
CONTROL**



Temperature range +12°C to +60°C (according to models).  
Compatible with all PLUS range viscometer.  
Rapid temperature setting of 600 ml and 150 ml beakers according to ISO 2555.

# Activity domains



Food Industry



Paint / ink / coatings



Car industry



Cosmetics pharmaceuticals



Chemical / petroleum products



Teaching

## AVAILABLE TEMPERATURE CONTROL DEVICES

Compatible only with bayonet coupling device

| Designation               | Part Number | Temperature range | Type    | Need Circulator <sup>a)</sup> | Prog. <sup>b)</sup> | Compatible device   | Compatible Measuring system | Size (pxlxh) in mm | Weight |
|---------------------------|-------------|-------------------|---------|-------------------------------|---------------------|---------------------|-----------------------------|--------------------|--------|
| EVA LR PLUS <sup>c)</sup> | N950006     | +15°C to +45°C    | Peltier | No                            | No                  | All                 | ASTM (L and R)              | 610x340x650        | 15Kg   |
| EVA BV PLUS <sup>d)</sup> | N950300     | +12°C to +60°C    | Peltier | No                            | No                  | FIRST, RM100, RM200 | MS-BV                       |                    |        |

a) Circulator not included. Need for cooling of liquid Peltier

b) Allow programming of temperature ramp

c) Usable with 600 ml beaker.

d) Usable with 150 ml beaker. Not compatible with all instruments version LR